



Safety Data Sheet

Issue Date: 01-Mar-2012

Revision Date: 19-Aug-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name ENGINE FLUSH

Other means of identification

SDS # BP-009

UN/ID No UN1268

Recommended use of the chemical and restrictions on use

Recommended Use Engine treatment.

Details of the supplier of the safety data sheet

Manufactured by:

Bell Performance, Inc.
1340 Bennett Drive
Longwood, FL 32750

Emergency Telephone Number

Company Phone Number 407-831-5021
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Amber liquid

Physical State Liquid

Odor Slight characteristic odor

Classification

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Hazards Not Otherwise Classified (HNOC)

Causes mild skin irritation

Signal Word

Danger

Hazard Statements

May cause genetic defects
May cause cancer
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Mineral Spirits	8052-41-3	Proprietary
1,2,4 Trimethylbenzene	95-63-6	Proprietary
Ethylene Glycol Monobutyl Ether	111-76-2	Proprietary
Xylene	1330-20-7	Proprietary
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Proprietary
Methylene chloride	75-09-2	Proprietary
Naphthalene	91-20-3	Proprietary

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If irritation persists, seek medical attention.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Ingestion	Do not induce vomiting. Rinse mouth. If the victim is conscious, immediately give 2 to 4 glasses of water. Immediately call a poison center or doctor/physician.

Most important symptoms and effects

Symptoms	May cause eye irritation. Prolonged or repeated contact may cause skin irritation. May aggravate pre-existing liver and kidney disorders. For Chronic Exposure. May cause Central Nervous System (CNS) depression. May cause respiratory irritation. Excessive inhalation may produce dizziness, nausea, headache, and incoordination.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Foam.

Unsuitable Extinguishing Media Water may be ineffective, but can be used to protect firefighter and cool containers.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors are heavier than air and may accumulate in low areas or areas inadequately ventilated. Vapors may also travel along the ground to be ignited at location distant from handling site; flashback of flame to handling site may occur. Never use welding or cutting torch on or near drum (even empty), because product (even just residue) can ignite explosively.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂).

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Observe all personal protection equipment recommendations described in Sections 5 & 8.
-----------------------------	--

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Take up with sand or other non-combustible absorbent material and place into containers for later disposal. Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Ground/bond container and receiving equipment. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from ignition sources and incompatible materials. Store locked up.

Incompatible Materials Strong oxidizing agents. Strong acids. Strong bases. Amines.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Methylene chloride 75-09-2	TWA: 50 ppm	TWA: 25 ppm (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm

Naphthalene 91-20-3	STEL: 15 ppm TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
------------------------	-----------------------------------	--	---

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical safety goggles/faceshield.

Skin and Body Protection Suitable protective clothing. Impervious gloves such as nitrile are recommended for operations which may result in prolonged or repeated skin contact.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Take off all contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Slight characteristic odor
Appearance	Amber liquid	Odor Threshold	Not determined
Color	Amber		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	158-208 °C / 278-392 °F		
Flash Point	38 °C / 102 °F		
Evaporation Rate	70		Pensky-Martens Closed Cup (PMCC) (Ether = 1)
Flammability (Solid, Gas)	Liquid-not applicable		
Upper Flammability Limits	6.0		
Lower Flammability Limit	1.0		
Vapor Pressure	2 mmHg		
Vapor Density	5.5		(Air=1)
Specific Gravity	0.817 @ 74 °F		(1=Water)
Water Solubility	0.1		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children. Keep away from sources of ignition such as heat, sparks or open flames.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Amines.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Causes mild skin irritation.

Inhalation Avoid breathing vapors or mists.

Ingestion Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
1,2,4 Trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
Methylene chloride 75-09-2	> 2000 mg/kg (Rat)	-	= 76000 mg/m ³ (Rat) 4 h
Lauryl Alcohol 112-53-8	> 5000 mg/kg (Rat)	-	-
Naphthalene 91-20-3	= 490 mg/kg (Rat)	> 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
1-Tetradecanol 112-72-1	> 5000 mg/kg (Rat)	> 5 g/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	A3	Group 3		
Xylene 1330-20-7		Group 3		
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	A2	Group 1		X
Methylene chloride 75-09-2	A3	Group 2B	Reasonably Anticipated	X
Naphthalene 91-20-3		Group 2B	Reasonably Anticipated	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
1,2,4 Trimethylbenzene 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through		6.14: 48 h Daphnia magna mg/L EC50
Ethylene Glycol Monobutyl Ether 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Methylene chloride 75-09-2	500: 96 h Pseudokirchneriella subcapitata mg/L EC50 500: 72 h Pseudokirchneriella subcapitata mg/L EC50	140.8 - 277.8: 96 h Pimephales promelas mg/L LC50 flow-through 262 - 855: 96 h Pimephales promelas mg/L LC50 static 193: 96 h Lepomis macrochirus mg/L LC50 static 193: 96 h Lepomis macrochirus mg/L LC50 flow-through	EC50 = 1 mg/L 24 h EC50 = 2.88 mg/L 15 min	1532 - 1847: 48 h Daphnia magna mg/L EC50 Static 190: 48 h Daphnia magna mg/L EC50
Lauryl Alcohol 112-53-8	0.62: 96 h Desmodesmus subspicatus mg/L EC50	1.01: 96 h Pimephales promelas mg/L LC50 flow-through 0.1855: 96 h Pimephales promelas mg/L LC50		320: 48 h Daphnia magna mg/L EC50
Naphthalene 91-20-3		5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static		2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static
1-Tetradecanol 112-72-1	10: 96 h Desmodesmus subspicatus mg/L EC50	10000: 96 h Brachydanio rerio mg/L LC50		

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
1,2,4 Trimethylbenzene 95-63-6	3.63
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
Xylene 1330-20-7	3.15
Methylene chloride 75-09-2	1.25
Naphthalene 91-20-3	3.3

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Methylene chloride 75-09-2	U080	Included in waste streams: F001, F002, F024, F025, F039, K009, K010, K156, K157, K158		U080
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Methylene chloride 75-09-2	Category I - Volatiles		Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
------------------------	--	--	--	--

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Methylene chloride 75-09-2	Toxic
Naphthalene 91-20-3	Toxic

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. Based on package size, product may be eligible for limited quantity exception.

DOT In containers of 119 gallons capacity or less this product is not regulated by DOT

UN/ID No UN1268

Proper Shipping Name Petroleum products, n.o.s. (Aliphatic Hydrocarbons)

Hazard Class 3

Packing Group III

IATA

UN/ID No UN1268

Proper Shipping Name Petroleum products, n.o.s. (Aliphatic Hydrocarbons)

Hazard Class 3

Packing Group III

IMDG

UN/ID No UN1268

Proper Shipping Name Petroleum products, n.o.s. (Aliphatic Hydrocarbons)

Hazard Class 3

Packing Group III

Marine Pollutant Manufacturer lists this product as "Not a marine pollutant"

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Methylene chloride 75-09-2	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Naphthalene 91-20-3	100 lb 1 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	Proprietary	1.0
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	Proprietary	1.0
Xylene - 1330-20-7	1330-20-7	Proprietary	1.0
Methylene chloride - 75-09-2	75-09-2	Proprietary	0.1
Naphthalene - 91-20-3	91-20-3	Proprietary	0.1

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7 (Proprietary)	100 lb			X
Methylene chloride 75-09-2 (Proprietary)		X	X	
Naphthalene 91-20-3 (Proprietary)	100 lb	X	X	X

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methylene chloride - 75-09-2	Carcinogen
Naphthalene - 91-20-3	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits 8052-41-3	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Xylene 1330-20-7	X	X	X
Methylene chloride 75-09-2	X	X	X
Naphthalene 91-20-3	X	X	X

16. OTHER INFORMATION

NFPA**Health Hazards**

2

Flammability

2

Instability

0

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical Hazards

Not determined

Personal Protection

Not determined

Issue Date:

01-Mar-2012

Revision Date:

19-Aug-2014

Revision Note:

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet