



BIO DEE-ZOL

ALL-PURPOSE MULTI-FUNCTION TREATMENT OPTIMIZED FOR BIODIESEL BLENDS.

For biodiesel users who are looking for a problem-solving fuel treatment to fix and prevent fuel-related problems brought on by biodiesel blends, your search is over.

BIO DEE-ZOL, Bell Performance's concentrated multi-purpose treatment for biodiesel blends, addresses all major fuel concerns of biodiesel users in one formulation.

Used in every tank, **BIO DEE-ZOL** improves mileage and performance, raises fuel cetane rating, controls water, cleans engines and improves the stability of biodiesel fuels in storage.

BIO DEE-ZOL helps you get the most out of your biodiesel fuels.

If you need these benefits along with cold weather protection check out Bio Dee-Zol Plus.

WHO SHOULD USE BIO DEE-ZOL?

If you need a highly effective all-purpose treatment for biodiesel blend fuels, **BIO DEE-ZOL** is for you.

IDEAL USERS AND USES OF THIS PRODUCT WILL INCLUDE:

- Anyone wanting to get better performance from biodiesel blended fuel
- Anyone seeking to reduce and eliminate common problems found with using biodiesel
- Diesel trucks and heavy equipment running on biodiesel blends
- Diesel generators
- Diesel fuel users using stored biodiesel blends
- Diesel boat operators
- Any engine or application running on biodiesel blend fuel

WHAT WILL BIO DEE-ZOL DO FOR YOU?

- Improves mileage and horsepower
- Raises fuel cetane number
- Cleans injectors and combustion chambers to remove biodiesel-related deposits
- Reduces pollutants and black smoke
- Improves DPF service intervals
- Controls water in biodiesel fuels
- Reduces filter-plugging caused by formation of biodiesel shellacs and varnishes
- Stabilizes biodiesel blends to protect their stored fuel quality and prevent darkening of stored fuels
- Yields better performance and easier cold starting

RECOMMENDED TREAT RATIO

Use one ounce to 10 gallons of fuel. One gallon treats up to 1,280 gallons of biodiesel blend fuel.

FOR OPTIMAL PERFORMANCE

BIO DEE-ZOL works best when well-mixed into fuel. To ensure optimal blending of fuel and treatment, splash blending and/or direct injection with fuel circulation is the recommended best practice.

When adding directly to the fuel tank, it is recommended to add **BIO DEE-ZOL** first, and then add fuel.

AVAILABILITY

BIO DEE-ZOL is available in 16 oz., 32 oz., 1 gallon, 5 gallon and 55-gallon product sizes.

Ideal for treatment of bulk volumes of stored biodiesel. Contact the Bell Performance office or speak to your Account Manager for more details on bulk availability and pricing.

